

SIGNAL GENERATOR / TRANSMITTER FEATURES

SIGNAL GENERATOR / TRANSMITTER FEATURES	SGA4	SGV4	MXT4
One Watt Power	●	●	●
Power Levels	2	4	4
Generator / Transmitter Frequencies:	●	●	●
33+131kHz (Connected and Induced)	●	●	●
131kHz (Connected and Induced)	-	-	●
33kHz (Connected and Induced)	-	-	●
8kHz (Connected and Induced)	-	-	●
512Hz (Connected)	-	-	●
640Hz (Connected)	-	-	●
Pulsed/ Continuous Output Signal	●	●	●
Signal Connection Modes	●	●	●
Direct Connection	●	●	●
Wraparound	●	●	●
Induction	●	●	●
Automatic Daily Self Test	-	●	●
Data Logging	-	●	●
Data Transfer via USB	-	●	●
High Resolution Backlit Liquid Crystal Display	-	●	●
No Periodic Calibration*	●	●	●
Three Year Warranty**	●	●	●
Batteries*** 4 x D (LR20) Alkaline or NiMH Rechargeable	●	●	●
In-Built Accessory Tray****	●	●	●
IP65	●	●	●

* No Periodic Calibration. The SGA4, SGV4 and MXT4 do not require periodic recalibration.

A Product Validation Certificate can be printed using the PC Toolkit.

C.Soope authorised Service Centres are also able to provide third-party Test and Calibration Certification should you require it to comply with client or internal regulations.

** Three Year warranty. Conditions apply.

*** Batteries. 4 x D LR20 Alkaline or NiMH Rechargeable batteries housed in a secure battery compartment.

**** In-Built Accessory Tray includes Direct Connection Lead, Auxiliary 10m Earth Lead, Connection Magnets, Earth Stake and Instruction Manual.

